

Eco-Line - Creperas - Baño maría



# Creperas

Crêpe makers



ELC-82G



Embutición protectora del interior  
Inlay to protect inside


- ▶ Medidas comunes: 50 cm de profundidad x 24 cm de altura. ▶ Diámetro útil de la placa: 350mm. ▶ Calor uniforme en toda la superficie de la placa. ▶ Placa de acero rectificando de 15mm de espesor. ⬠ Quemador de estrella de gran rendimiento. ▶ Válvulas de gas con termopar de seguridad. ⚡ Resistencia blindada en acero inoxidable. ▶ Control de la temperatura a través del termostato.
- ▶ Common dimensions: 50 cm depth x 24 height. ▶ Useful diameter of the plate: 350 mm. ▶ Even heat on the entire plate. ▶ Blued steel plate 15 mm thick. ⬠ High performance star burner. ▶ Gas valves with safety thermocouple. ⚡ Stainless steel shielded heating element.

**Modelos ELC-EM - Monofásico 230V 50/60Hz**  
ELC-EM Models - Single-phase 230V 50/60Hz

Modelos	Medidas exteriores	Diámetro placa	Kg neto	kW	Kcal/h	Medidas embalaje	Kg bruto	m <sup>3</sup>
ELC-41 G	40x50x24h	∅ 35	19	5,5	4.675	42x64x41h	22	0,11
ELC-82 G	80x50x24h	∅ 35 + ∅ 35	35	11	9.350	96x64x48h	45	0,29
ELC-41 EM	40x50x24h	∅ 35	20	2,4	-	42x64x41h	23	0,11
ELC-82 EM	80x50x24h	∅ 35 + ∅ 35	38	4,8	-	96x64x48h	48	0,29

Situación conexión  
Connection situation

● Gas 1/2" ● Eléctrico



# Baño maría

Electric bain marie




ELBM-31 EM

- ▶ Medidas comunes: 50cm de profundidad x 24 cm de altura. ▶ Termostato de trabajo 30-90°C. ▶ Dotado de grifo de vaciado. ▶ Cubetas **NO INCLUIDAS**. ▶ Resistencia blindada en acero inoxidable. ▶ Plancha inox perforada en el interior.
- ▶ Common dimensions: 50 cm depth x 24 height ▶ Work thermostat 30-90 °C ▶ Equipped with drain tap ▶ Basins **NOT INCLUDED** ▶ Stainless steel shielded heating element. ▶ Perforated stainless steel plate on the inside.

Situación conexión  
Connection situation

● Eléctrico



Modelo	Medidas exteriores	Medidas cuba	Kg neto	kW	Medidas embalaje	Kg bruto	m <sup>3</sup>
ELBM-31 EM	30x50x24h	GN 1/2 x 15h	8	0,9	37x64x35h	10	0,08



Monofásico 230V 50/60 Hz  
Single-phase 230V 50/60 Hz