



MFPP-140



MFCP-140

El precio incluye vitrina de ingredientes - *Topping unit included in price*



Cubetas GN y perfiles divisorios NO incluidos en el precio, ver página 416  
*GN containers and dividers NOT included in price, see page 416*

| mod.     | rango<br>range<br>°C | largo<br>length<br>(mm) | alto<br>height<br>(mm) | fondo<br>depth<br>(mm) | estantes<br>shelves | pares guías<br>slides sets | capacidad GN<br>GN capacity<br>1/4 | volumen<br>capacity<br>(L) | voltaje<br>voltage | refrigerante<br>refrigerant | potencia frig.<br>frig. power<br>W | potencia<br>power<br>W |
|----------|----------------------|-------------------------|------------------------|------------------------|---------------------|----------------------------|------------------------------------|----------------------------|--------------------|-----------------------------|------------------------------------|------------------------|
| MFPP-140 | 0°C<br>+8°C          | 1370                    | 890                    | 700                    | 3                   | 3                          | 5                                  | 264                        | 230V-50Hz          | R290                        | 845                                | 490                    |
| MFCP-140 | 0°C<br>+8°C          | 1370                    | 970                    | 700                    | 3                   | 3                          | 5                                  | 399                        | 230V-50Hz          | R290                        | 845                                | 490                    |

Características técnicas y constructivas sujetas a variación sin previo aviso.

- Exterior en acero inox AISI-304
- Interior en acero inox AISI-304, con aristas curvas y fondo embutido
- Puertas de apertura reversible, con sistema de cierre automático y burlete magnético (permanece abierta al superar los 90° de apertura)
- Encimera de granito, con peto trasero y laterales de 180 mm
- Estantes interiores GN 1/1 de alambre en acero plastificado, regulables en altura
- Unidad condensadora ventilada y extraíble
- Evaporador sistema tiro forzado, con recubrimiento epoxi anticorrosión
- Evaporación automática del agua de descarche
- Aislamiento de poliuretano inyectado, densidad 40 Kg/m³, cero efectos ODP y GWP
- Control digital de temperatura, descarches optimizados, alarma por alta temperatura de condensación. Eficiente gestión del consumo de energía
- Expositor de ingredientes independiente, capacidad GN 1/4, incluido
- Temperatura de trabajo 32°C ambiente

We reserve the right to change specifications without prior notice.

- AISI-304 stainless steel exterior
- AISI-304 stainless steel interior, stamped bottom and rounded corners
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Granite working surface with 180 mm upstands
- GN 1/1 shelves made of plasticized steel wire, height adjustable
- Removable and fan assisted condenser unit
- Fan assisted evaporator, with epoxi anticorrosion coating.
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost, high-temperature condensation alarm. Efficient management of energy consumption
- GN 1/4 topping unit, included
- Operating temperature 32°C ambient



Incremento precio por cambio de puerta a cajonera **doble**, desmontable sobre guías inox telescópicas, sistema auto-cierre

*Increase of price by changing door to double drawers set, detachable telescopic SS runners, soft-closing system*

MFPP

MFCP



evaporador central  
double fan evaporator

cajones opcionales  
optimal drawers

## OPCIONES

## OPTIONS

|                               |                              |
|-------------------------------|------------------------------|
| parrilla adicional GN-1/1     | additional shelf GN-1/1      |
| set adicional guías GN-1/1    | additional set GN-1/1 slides |
| set 4 ruedas                  | set 4 wheels                 |
| cerradura puerta inox         | SS door lock                 |
| APPC                          | HACCP                        |
| 230V 60Hz / 115V 60Hz         | 230V 60Hz / 115V 60Hz        |
| sin expositor de ingredientes | without ingredient display   |

Expositor topping con  
iluminación LED  
LED lighting topping unit





MFCP-140

