



AGRE-751-PF
ACGE-751-PF



AGRE-1002-PF
ACGE-1002-PF



AGRE-2003
ACGE-2003

mod.	rango range °C	largo length (mm)	alto height (mm)	fondo depth (mm)	estantes shelves GN 2/1	niveles embutidos stamped levels	guías slides	volumen capacity (L)	voltaje voltage	refrigerante refrigerant	potencia frig. frig. power W	potencia power W	CCE EEC 2015/1094 EN16825	clase climate 2015/1094 EN16825
AGRE-751-PF	-2°C +8°C	680	2130	860	4	24	-	645	230V-50Hz	R290	502	260	C	5 40°C 40%
ACGE-751-PF	-20°C -15°C	680	2130	860	4	24	-	645	230V-50Hz	R290	606	560	E	4 30°C 55%
AGRE-1002-PF	-2°C +8°C	1370	2130	860	8	24	6	1404	230V-50Hz	R290	845	396	D	4 30°C 55%
ACGE-1002-PF	-20°C -15°C	1370	2130	860	8	24	6	1282	230V-50Hz	R290	907	902	E	4 30°C 55%
AGRE-2003	-2°C +8°C	2055	2130	860	12	-	24	2197	230V-50Hz	R290	1702	943	E	4 30°C 55%
ACGE-2003	-20°C -15°C	2055	2130	860	12	-	24	2197	230V-50Hz	R290	1814	1726	E	3 25°C 60%

Características técnicas y constructivas sujetas a variación sin previo aviso.

Modelos 750 y 1000: costados embutidos
Modelos 2000: cremalleras + guías inox

- Exterior en acero inox AISI-304, excepto el respaldo y fondo
- Interior en acero inox AISI-304, con aristas curvas y fondo embutido
- Puertas de apertura reversible (751), con sistema de cierre automático y burlete magnético (permanece abierta al superar los 90° de apertura)
- Cerradura con llave, de serie
- **AGRE:** Doble cristal + LEDs, **ACGE:** Triple cristal + LEDs
- Estantes parrilla reforzados GN 2/1, de acero plastificado
- Pies en tubo de acero inox ajustables en altura 135- 200 mm
- Cuadro de mandos elevable
- Unidad condensadora ventilada
- Evaporador sistema tiro forzado, con recubrimiento epoxi anticorrosión
- Paro ventiladores tiro forzado al abrir la puerta
- Evaporación automática del agua de descarche
- Poliuretano inyectado, densidad 40 Kg/m³, cero efectos ODP y GWP
- 75 mm aislamiento perimetral
- Control digital de temperatura, descarches optimizados, alarma por puerta abierta y alta temperatura de condensación. Eficiente gestión del consumo de energía
- Temperatura de trabajo a 32°C ambiente

We reserve the right to change specifications without prior notice.

750 and 1000: pressformed sides
2000: racks + SS slides

- AISI-304 stainless steel exterior, except rear side and base
- AISI-304 stainless steel interior, stamped bottom and rounded corners
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense (751)
- Key lock as standard
- **AGRE:** Double glazed door + LEDs, **ACGE:** Triple glazed door + LEDs
- Reinforced GN 2/1 shelves made of plasticized steel
- AISI -304 adjustable legs, 135 to 200 mm
- Lifiable control panel
- Fan assisted condenser unit
- Fan assisted evaporator, with epoxi anticorrosion coating
- Evaporator fan stops when door is opened
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane, zero ODP and GWP
- 75 mm perimetral insulation
- Digital temperature control, optimized defrost, door open and high-temperature condensation alarms. Efficient management of energy consumption
- Operating temperature 32°C ambient



OPCIONES	OPTIONS
parrilla adicional GN-2/1	additional shelf GN-2/1
parrilla adicional GN-2/1 + guía	additional shelf GN-2/1 + slide
par guías adicionales GN-2/1	additional slidet GN-2/1
barras carniceras	meat bars
set 4 ruedas	set 4 wheels
set 5 ruedas	set 5 wheels
set 6 ruedas	set 6 wheels
respaldo inox	SS rear side
tropicalizado 43°C	tropicalized 43 °C
230V 60Hz / 115V 60Hz	230V 60Hz / 115V 60Hz
pedal apertura puerta	door opening pedal
APPC	HACCP

