

Freidoras Gas Free Standing-GW

Modelo Model	Dimensiones (L x P x A) Dimensions (W x D x H) mm	Dimensiones Cesto (L x P x A) Basket Dimensions (W x D x H) mm	Potencia Power kW	Cantidad Aceite Oil Quantity l.	Patatas Congeladas Frozen Potatoes kg/h	Capacidad Bidón Recogida Aceite Oil Collection Drum Capacity l.
GW20T	400 x 700 x 1139	215 x 375 x 120	12	17	18	20
GWD20T	700 x 700 x 1139	2 x (215 x 375 x 120)	12 + 12	17 + 17	36	20 + 20
GWM35T	700 x 700 x 1139	2 x (365 x 265 x 120)	19	35 / 46	-	40
GW209T*	400 x 900 x 1139	215 x 375 x 120	12	17	18	20
GWD209T*	800 x 900 x 1139	2 x (215 x 375 x 120)	12 + 12	17 + 17	36	20 + 20

*Modelos modulares de 900mm 900mm modular models

CARACTERÍSTICAS FEATURES

Cuba embutida sin soldaduras, facilitando una rápida y completa limpieza, con una amplia zona fría. Bidón para recuperación del aceite de acero inoxidable con filtro superior extraíble. Grifo de descarga de latón cromado con dispositivo de seguridad contra aberturas accidentales. Termostato para la regulación de la temperatura del aceite de 90 hasta 195°C. Termostato de seguridad adicional a calibración fija (+ 220°C)

Resistencias blindadas de acero inoxidable.

Seamless pressed tank, enabling quick and complete cleaning, with a large cold zone. Stainless steel oil recovery drum with removable upper filter. Chromed brass drain cock with safety device prevents accidental opening. Oil temperature regulation thermostat from 90°C to 195°C. Additional fixed calibration safety thermostat (+ 220°C)

Armoured stainless steel heating elements



GWD20T

