


03 ARMARIO DE REFRIGERACIÓN Y CONGELACIÓN GN 2/1 600/1300 L. GN 2/1 REFRIGERATOR AND FREEZER REACH IN 600/1300 L.

03 Armarios

EXTERIOR

- Acero Inox AISI 304 18/10
- Respaldo en chapa galvanizada

INTERIOR

- Acero Inox AISI 304 18/10
- Desagüe interior
- Fondo embutido con amplios radios
- Iluminación LED 
- Parrillas de alambre de acero plastificado (530x650), regulables en altura y fácilmente desmontables
- Marcos puerta calefactados para evitar acumulación de hielo (BT)

AISLAMIENTO

- Poliuretano inyectado alta presión libre de CFC´s densidad 40 kg/m³, bajo GWP y cero efecto ODP

PUERTAS

- Contrapuerta embutida
- Burlete de triple cámara fácilmente sustituible
- Puertas con tirador integrado
- Bisagra pivotante con bloqueo de apertura

RUEDAS

- Diámetro 100 mm. Delanteras con freno

REFRIGERACIÓN


- Sistema de refrigeración compacto Monobloc, INFRIBLOCK
- Evaporadores tratados anticorrosión 100% Poliéster
- Bandeja evaporativa
- Control temperatura final del desescarche
- Desescarche por gas caliente (BT)



EXTERIOR

- AISI 304 18/10 stainless steel
- Galvanized steel back

INTERIOR

- AISI 304 18/10 stainless steel
- Internal drain
- Sealed interior floors and rounded cabinet corners
- LED Lighting 
- Plastic coated Wire shelves (530x650), adjustable height and easy removal
- Heated door frame to avoid accumulation of ice (BT)

INSULATION

- Free CFC's high density [40kg/m³] polyurethane insulation with low GWP & zero ODP effect

DOORS

- Stamped rear door
- Easy removal triple chamber gasket
- Integrated handle doors
- Self closing doors with stay open feature

CASTERS

- 100 mm diameter. Front brake casters

REFRIGERATION

- Compact refrigeration system Monobloc
- Evaporator coil coated with anti-corrosion material 100% Polyester
- Evaporative tray
- Control of the final defrost temperature
- Hot gas defrost (BT)

MODELOS MODELS	Dimensiones Dimensions LxPxH (mm)	Potencia Power (W)	Electrica Electrical (V/Hz)	Capacidad Capacity (L)	Puertas Doors	Nº parrillas / J. guías No shelves / Slides	Poder de congelación Freezing power (Kg/24h)	Compresor Compressor (HP)	Potencia frig. Cooling capacity (W a -10°C)	Consumo Consumption (kWh/24h)	Evaporación Evaporation	Régimen T ^{RA} (38°C)	Desescarche Defrost	Control Control	Refrigerante Refrigerant
AGB 651	687x794x1969	585	220/50	535	1	3/3 (530x650)	-	1/3	395	2,95	Forzada Forced	-2°C/+8°C	Automático Automatic	Digital 30 AMP	R 134 a
AGB 1302	1385x794x1969	945	220/50	1180	2	6/6 (530x650)	-	1/2	568	5,38	Forzada Forced	-2°C/+8°C	Automático Automatic	Digital 30 AMP	R 134 a
AGB 601 BT	687x794x1969	1000	220/50	535	1	3/3 (530x650)	2,5	5/8	542	4,24	Forzada Forced	-18°C	Automático Automatic	Digital 30 AMP	R 404 A
AGB 1302 BT	1385x794x1969	1390	220/50	1180	2	6/6 (530x650)	5	1 1/4	1161	8,21	Forzada Forced	-18°C	Automático Automatic	Digital 30 AMP	R 404 A

Características técnicas y constructivas sujetas a variación sin previo aviso / We reserve the right to change specifications without prior notice.

ARMARIO DE REFRIGERACIÓN Y CONGELACIÓN GN 2/1 600/1300 L.
 GN 2/1 REFRIGERATOR AND FREEZER REACH IN 600/1300 L.

I INFRIBLOCK



03 Armarios



AGB 1302 BT




AGB 651

OPCIONAL / OPTIONAL


- Parrilla / Wire shelf (502X14) **39 €**
- Juego de guías / Slides (503X02; 503X03) **28 €**
- Cerradura / Lock (506X120; 506X121) **29 €**
- Ruedas / Casters (705X16=2; 705X17=2) **145 €**
- Eco Efficiency **+8%** **R-290**

eco **-29%**
 Efficiency Ahorro Energía / Energy Saving




AGB 651

1.937 €




AGB 1302

2.541 €



AGB 651 BT

2.483 €



AGB 1302 BT

3.225 €


03 ARMARIO DE REFRIGERACIÓN Y CONGELACIÓN GN 2/1 700/1400 L. GN 2/1 REFRIGERATOR AND FREEZER REACH IN 700/1400 L.

03 Armarios

EXTERIOR

- Acero Inox AISI 304 18/10
- Respaldo en chapa galvanizada

INTERIOR

- Acero Inox AISI 304 18/10
- Desagüe interior
- Fondo embutido con amplios radios
- Iluminación LED 
- Parrillas de alambre de acero plastificado (530x650), regulables en altura y fácilmente desmontables
- Marcos puerta calefactados para evitar acumulación de hielo (BT)

AISLAMIENTO

- Poliuretano inyectado alta presión libre de CFC's densidad 40 kg/m³, bajo GWP y cero efecto ODP

PUERTAS

- Contrapuerta embutida
- Bultete de triple cámara fácilmente sustituible
- Puertas con tirador integrado
- Bisagra pivotante con bloqueo de apertura
- Puertas con doble acristalamiento (6-15-5)
- Puertas con triple acristalamiento (4-8-3-8-3) (BT/CR)

PATAS

- Patas en acero inox regulables en altura hasta 200 mm

REFRIGERACIÓN

- Sistema de refrigeración compacto Monobloc, INFRIBLOCK
- Evaporadores tratados anticorrosión 100% Poliéster
- Bandeja evaporativa
- Control temperatura final del desescarche
- Desescarche por gas caliente (BT)




I INFRIBLOCK

EXTERIOR

- AISI 304 18/10 stainless steel
- Galvanized steel back

INTERIOR

- AISI 304 18/10 stainless steel
- Internal drain
- Sealed interior floors and rounded cabinet corners
- LED Lighting 
- Plastic coated Wire shelves (530x650), adjustable height and easy removal
- Heated door frame to avoid accumulation of ice (BT)

INSULATION

- Free CFC's high density (40kg/m³) polyurethane insulation with low GWP & zero ODP effect

DOORS
















- Stamped rear door
- Easy removal triple chamber gasket
- Integrated handle doors
- Self closing doors with stay open feature
- Doors with double pane glass (6-15-5)
- Doors with heated triple pane glass (4-8-3-8-3) (BT/CR)

LEGS

- Stainless steel adjustable legs up to 200 mm

REFRIGERATION

- Compact refrigeration system Monobloc
- Evaporator coil coated with anti-corrosion material 100% Polyester
- Evaporative tray
- Control of the final defrost temperature
- Hot gas defrost (BT)

MODELOS MODELS															
	Dimensiones LxPxH (mm)	Potencia Power (W)	Eléctrica Electrical (V/Hz)	Capacidad Capacity (L)	Puertas Doors	Nº parrillas / J. guías No shelves / Slides	Poder de congelación Freezing power (Kg/24h)	Compresor Compressor (HP)	Potencia frig. Cooling capacity (W a -10°C)	Consumo Consumption (kWh/24h)	Evaporación Evaporation	Régimen T ^{int} (38°C)	Desescarche Defrost	Control Control	Refrigerante Refrigerant
AGB 701	687x794x2130	585	220/50	610	1	3/3 (530x650)	-	1/3	395	3,23	Forzada Forced	-2°C/+8°C	Automático Automatic	Digital 30 AMP	R 134 a
AGB 1402	1385x794x2130	945	220/50	1340	2	6/6 (530x650)	-	1/2	568	4,31	Forzada Forced	-2°C/+8°C	Automático Automatic	Digital 30 AMP	R 134 a
AGB 701 BT	687x794x2130	1000	220/50	610	1	3/3 (530x650)	2,5	5/8	542	7,92	Forzada Forced	-18°C	Automático Automatic	Digital 30 AMP	R 404 A
AGB 1402 BT	1385x794x2130	1390	220/50	1340	2	6/6 (530x650)	5	1 1/4	1161	9,67	Forzada Forced	-18°C	Automático Automatic	Digital 30 AMP	R 404 A

Características técnicas y constructivas sujetas a variación sin previo aviso / We reserve the right to change specifications without prior notice.

ARMARIO DE REFRIGERACIÓN Y CONGELACIÓN GN 2/1 700/1400 L.
 GN 2/1 REFRIGERATOR AND FREEZER REACH IN 700/1400 L.

I INFRIBLOCK



AGB 701




AGB 1402 BT

03 Armarios

OPCIONAL / OPTIONAL


- Parrilla / Wire shelf (502X14) **39 €**
- Juego de guías / Slides (503X02; 503X03) **28 €**
- Cerradura / Lock (506X120; 506X121) **29 €**
- Eco Efficiency **+8%** R-290

eco **-29%**
 Efficiency Ahorro Energía / Energy Saving




AGB 701

2.057 €




AGB 1402

3.155 €



AGB 701 BT

2.749 €



AGB 1402 BT

3.908 €