

		Model	LP4060	
		Code Production	New	
Interface :				
				
	Overall Dimension (Width-Depth-Height) *open		mm	600 - 700(1135*) - 1228
	Packaging Dimension (WxDxH)		mm	700x800x1250
	Gross weight		Kg	80
	Net weight		Kg	74
	Volume		mc	0,6
	Rack size		mm	500 x 600
	Max door /hood opening		mm	405
	Max glasses/plate Height		mm	380
	Rack's drives/frame construction			flat
	Flanks construction			double skin
	Door/hood Construction			double skin
	Tank construction			deep drawn
	Tank volume		liter	23
	Tank heating element		W	2.100
	Tank surface strainers			stainless steel
	Wash pump type			double flow
	Wash pump power		W	700
	Soft start			YES
	Wash temperature		°C	60 (55-->65)
	Boiler type			without pressure
	Boiler volume		liter	7
	Back-flow system			break tank
	Boiler heating element		W	6.000
	Rinse booster pump			YES
	Rinse booster pump power		W	200
	Rinse temperature		°C	80 (80-->85)
	Rinse water consumption		Liter /rack	2,4
	Optimal external water pressure		bar	1 - 6
	Drain system			deep drain
	Drain filter			double filter
	Drain pump			standard built in
	Rinse aid dispenser			YES
	Detergent dispenser			YES
	Wash cycle		sec	120 - 240 - 360 - 720
	Special cycle		programs	n°6
	Self cleaning cycle			YES
	Electric Power		W	6.700
	Electric Connection		V - ph - Hz	400V 3N 50Hz
	Fuse		A	16
	Flat Rack in stainless steel 50x60		N°1	706129
	Grid for trays		N°	optional
	Electric cable			YES
	Drain hose			YES
	Fill hose			YES

