

FHC20AHC/WHC



CARACTERÍSTICAS PRINCIPALES / MAIN FEATURES / PRINCIPALES CARACTÉRISTIQUES

- ✓ Cubo compacto y cristalino/ Compact and crystal cube/ Cubes compacts et cristallins.
- ✓ Acero inoxidable AISI 304 Acabado Scotch Brite/ AISI 304 SS Scotch Brite finish/AISI 304 SS Scotch Brite finish.
- ✓ Clase tropical +43°C/ Tropical class +43°C / Classe tropicale +43°C.
- ✓ Filtro anticalcáreo fácil de limpiar/ Cleanable antiscala filter/ Filtre anti-calcaire facile à nettoyer.
- ✓ Sistema de refrigeración por aire o por agua/ Air or water cooling system/ Système de refroidissement par air ou par eau.
- ✓ Superficies internas redondeadas fáciles de limpiar/ Easy cleanable internal rounded surfaces/Surfaces internes arrondies faciles à nettoyer.
- ✓ Almacenamiento aislado sin HCFC/ HCFC-Free insulated storage/ Stockage isolé sans HCFC.
- ✓ Funcionamiento electromecánico/ Electromechanical operation/ Fonctionnement électromécanique.
- ✓ Sistema de lavado automático/ Automatic washing system/ Système de rinçage automatique.

FHC20AHC/WHC

	FHC20AHC/WHC															
Medidas LxFxA/Dimensions LxDxH/Dimensions (L-P-H mm)	355 x 404 x 590															
Medidas de embalaje/ Packing measures / Mesures d'emballage (L-P-H mm)	415 x 445 x 780															
Peso neto/Net Weight/ Poids net (kg)	27, 5 kg															
Peso bruto/Gross Weight/Poids brut (kg)	34 kg															
Acabado/ Finish/ Finition	AISI 304 stainless steel, scotch brite - ABS blue or grey															
Datos técnicos/Technical Features/ Informations techniques																
Producción en 24h / Production in 24h / Production en 24h	21 kg															
Capacidad de almacenamiento/ Store capacity up to/ Capacité de stockage	4 kg															
Sistema de refrigeración/ Cooling system/ Système de refroidissement	A - W															
Tipo de cubo/ Kind of cube/ Type de seau	D-13g															
Refrigerante/ Refrigerant/ Refrigerant	R290															
Tensión/Power/Tension	220-240 V ~ 50 Hz															
Potencia/Power/Puissance (kW)	35 kWh/100kg															
Conexionado / Connections / Connexions																
Todas las medidas se refieren a la esquina inferior izquierda trasera (L-H-Ø)/ All measures are referred to the rear bottom-left corner (L-H-Ø)/ Toutes les mesures sont rapportées au coin arrière inférieur gauche (L-H-Ø)																
1. Water in.: 88 mm / 3 7/16" - 184 mm / 7 4/16" - 3/4" 2. Water out.: 45 mm / 1 12/16" - 138 mm / 5 7/16" - 24 mm / 15/16" 3. Conexiones eléctricas /Electrical connections: 41 mm / 1 10/16" - 73 mm / 2 14/16"																
Condiciones de trabajo/ Working conditions/ Conditions de travail																
	<table><tr><td></td><td>Min</td><td>Max</td></tr><tr><td>Ambient temperature</td><td>+10° C / +50° F</td><td>+43° C / 110° F</td></tr><tr><td>Water temperature</td><td>+3° C / +37° F</td><td>+32° C / +90° F</td></tr><tr><td>Voltage</td><td>-10%</td><td>+10%</td></tr><tr><td>Water inlet pressure</td><td>1bar (14 psi)</td><td>6bar (84 psi)</td></tr></table>		Min	Max	Ambient temperature	+10° C / +50° F	+43° C / 110° F	Water temperature	+3° C / +37° F	+32° C / +90° F	Voltage	-10%	+10%	Water inlet pressure	1bar (14 psi)	6bar (84 psi)
	Min	Max														
Ambient temperature	+10° C / +50° F	+43° C / 110° F														
Water temperature	+3° C / +37° F	+32° C / +90° F														
Voltage	-10%	+10%														
Water inlet pressure	1bar (14 psi)	6bar (84 psi)														

Rendimiento/ Performances/ Performance

		Water temperature					
		7° C	45° F	15° C	60° F	21° C	70° F
Air temperature	10° C	23 kg					
	50° F		51 lbs				
	21° C			21 kg			
	70° F				46 lbs		
	32° C					16 kg	
	90° F						35 lbs

Características / Features / Caractéristiques

Interruptor basculante ON-OFF/ ON-OFF rocker switch/
 Interrupteur à bascule ON-OFF
 Voltaje estándar y especiales/ Standard and special voltages/
 Tensions standard et spéciales
 Corredera de pulverización/ Patented sprayer slide/ Glissière de
 pulvérisation brevetée
 Sin HFC/ HFC Free/ Sans HFC

