



## FREIDORAS DE ALTA CAPACIDAD

Fryers high capacity



### FREIDORA FOGÓN AUTOMÁTICA GAS

Máquina automática para gran producción o como equipo profesional. Por su calidad se trata de una máquina muy duradera y resistente para su uso industrial.

#### Características técnicas:

- Cuerpo en acero inoxidable Aisi 304 18/10.
- Cuba en acero inoxidable Aisi 304 18/10 integrada en el cuerpo.
- Ruedas para facilitar su desplazamiento.
- Quemador industrial de alta potencia controlado mediante un digital y sonda de temperatura. Apto para su uso en exterior e interior.
- Termostato digital de máxima precisión [+/-1°].
- Aislamiento de manta térmica de alta temperatura SUPER WOLL densidad 128kg/m3 espesor 13mm., excepto chimeneas.
- Chimeneas de expulsión de humos en acero inoxidable AISI 304, para colgar dosificadora o cortadora de patatas.
- Válvula de vaciado de aceite 1".
- Combustible butano / propano / gas ciudad.

#### Opcional:

- Fabricación especial en cuanto a las dimensiones, profundidad de la cuba o forma cónica o cilíndrica.
- Tapadera.
- Mástil para colgar dosificadora o cortadora de patatas.
- Aislamiento de chimeneas.

### Automatic Gas Fryers

Robust and resistant stainless steel industrial machines ideal for a big production, professional analog equipment.

#### Technical features:

- Manufactured of Aisi 304 18/10 stainless steel.
- Fryng in stainless steel AISI 304 18/10 integrated in the body.
- Wheels for easy movement.
- Industrial automatic burner controlled by a digital temperature probe.
- High precision digital thermost [+/-1°].
- Insulation of high temperature thermal blanket Woll SUPER 13mm. thick 128kg/m3 density, except chimneys.
- Chimney flue exhaust in stainless steel AISI 30, extuder for hanging or cutting potatoes.
- Oil drain valve 1".
- Useful inside, burner automatic.
- Combustible butane / propane / gas city.

#### Optional:

- Special manufacture in terms of dimensions, depth of the tub or conical or cylindrical shape.
- Optional support for hanging churros or potatoes machine.
- Container lid.
- Insulated chimneys.

MODELO Model	CAPACIDAD Capacity	Ø SUPERIOR Ø Outside	Ø INFERIOR Ø Inside	ALTURA SARTÉN Inside diameters	LARGO Lengt	ANCHO Width	ALTO High	POTENCIA Power	TIPO GAS Type gas
FGAUT70	14 L	600 mm.	400 mm.	170 mm.	700 mm.	700 mm.	800 mm.	37 KW	Butane/Propane/Gas Natural
FGAUT80	22 L	700 mm.	500 mm.	170 mm.	800 mm.	800 mm.	800 mm.	37 KW	Butane/Propane/Gas Natural
FGAUT90	30 L	800 mm.	600 mm.	170 mm.	900 mm.	900 mm.	800 mm.	37 KW	Butane/Propane/Gas Natural
FGAUT100	38 L	900 mm.	700 mm.	170 mm.	1000 mm.	1000 mm.	800 mm.	37 KW	Butane/Propane/Gas Natural

· Tapadera: Fogón de 70 cm.: 190 € / Fogón de 80 cm.: 210 € / Fogón de 90 cm.: 230 € / Fogón de 100 cm.: 250 €