

LAVADO
WASHING
LAVAGE

SERIE PREMIUM EC

CICLO ESPECIAL CRISTALERÍA
SPECIAL GLASSWARE CYCLE
CYCLE SPÉCIAL VERRE



Premium line EC



Modelo

Model

Modèle

GS - 6 AF EC

GS - 18 EC

GS - 19 EC

GS - 83 EC

Características Caracteristics Caractéristiques	Línea / Line / Ligne	 Premium line EC	 Premium line EC	 Premium line EC	 Premium line EC
	Medidas exteriores External measures Mesures extérieures (mm)	480 x 555 x 740	580 x 650 x 820	580 x 650 x 820	755 x 850 x 1480
	Producción copas h Production glasses h Production verres h	360	600	600	600
	Dimensiones cesta Rack measure Dimensions panier (mm)	400 x 400	500 x 500	500 x 500	500 x 500
	Altura útil Usable height Passage utile (mm)	290	380	380	440
	Potencia total Total power Puissance totale (Kw)	3,11	3,28	6,28	6,75 (9,75*)
	Potencia resistencia calderin Boiler heating element Puissance résistance chauffeur (Kw)	3	3	6	6 (9*) * Opcional / Optional / Optionnel
	Potencia resistencia cuba Tank heater power Puissance résistance cuve (Kw)	2,4	2,4	4,5	6
	Potencia bomba lavado Wash pump power Puissance pompe lavage (Kw)	0,11	0,28	0,28	0,75
	Voltaje Voltage Tension (V)	230 V mono 50 Hz / 60 Hz	230 V mono 50 Hz / 60 Hz	400 V III + N / 230 V III 50 Hz / 60 Hz	400 V III + N / 230 V III 50 Hz / 60 Hz

[illegible]

* Bomba de aclarado incluida. Air break no incluido, opcional. / Rinse pump included. Air break not included, optional.
/ Pompe de rinçage incluse. Air break non inclus, en option.