



Serie Euro-Snack Gas

Rectificado - Rectified steel






PL-90 N



Chimenea de fundición de fácil extracción y limpieza
Easy to remove and clean cast iron flue

- ▶ **Placa de acero rectificado** de 20 mm de espesor.
- ▶ Cajones recolectores de grasas en ambos laterales.
- ⬮ Encendido por tren de chispas a batería. ▶ Válvulas de gas con termopar de seguridad y llama piloto.
- ▶ **Semi-ranurados:** Modelo PLR-60 tiene 30 cm de ranurado. Modelos PLR-90 y PLR-120 tienen 40 cm.
- ▶ **Ranurados:** Modelos PLRR

- ▶ **Rectified steel plate** 20 mm thick.
- ▶ Fat collection drawers on both sides.
- ⬮ Ignition by sparks to battery. ▶ EURO-SIT thermocouple valves with pilot light.
- ▶ **Half-Slotted:** PLR-60 model has 30 cm of slots. PLR-90 and PLR-120 models are 40 cm.

<p>Tipo de placa Type of plate</p>	 PL Placa lisa Smooth plate	 PLR Placa semi-ranurada Half-slotted plate	 PLRR Placa ranurada Slotted plate
--	--	--	--

EN DOTACIÓN - INCLUDED

- Espátula pequeña
- **Modelos ranurados:**
- Espátula ranurada
- All models - Spatula
- Grooved models:
- Grooved spatula

Modelos	Medidas exteriores	Superficie útil	Kg neto	kW	Kcal/h	Medidas embalaje	Kg bruto	m ³
PL-60 N	61x60x25h	60x50	72	11	9.460	65x67x52h	80	0,23
PL-90 N	91x60x25h	90x50	105	19	16.340	95x67x54h	115	0,34
PL-120 N	121x60x25h	120x50	135	22	18.820	125x67x54h	147	0,45
PLR-60 N	61x60x25h	60x50	72	11	9.460	65x67x52h	80	0,23
PLR-90 N	91x60x25h	90x50	105	19	16.340	95x67x54h	115	0,34
PLR-120 N	121x60x25h	120x50	135	22	18.820	125x67x54h	147	0,45
PLRR-60 N	61x60x25h	60x50	72	11	9.460	65x67x52h	80	0,23
PLRR-90 N	91x60x25h	90x50	105	19	16.340	95x67x54h	115	0,34
PLRR-120 N	121x60x25h	120x50	135	22	18.820	125x67x54h	147	0,45

Situación conexión
Connection situation

- Gas 60: 1/2" - 90-120: 3/4"

