

FTH 30 E



FTRC 30 E



FTH 60 E



FTHRC 60 E



**CARACTERÍSTICAS TÉCNICAS**

Homologación CE.  
Ancho estándar GN de 33, 66 Y 99 cm.  
1, 2 o 3 zonas de cocción independiente.  
Superficie lisa, ranurada o combinada.  
Opcion cromoduro.  
Cajon recoge grasa de 1,5 l.

**TECHNICAL CHARACTERISTICS**

EC Approval.  
GN standard width of 33, 66 & 99cm.  
1, 2 or 3 independent cooking zones.  
Smooth, ribbed or combined plate surfaces.  
Hard-chrome option for each type of plate available.  
Waste drawer of 1,5 litres.

Modelo Model	L x An x Alt L x W x H (mm.)	Potencia (kW) Power (kW)	Espesor placa Plate thickness (mm)	Acabado Surface	Material Material	Regulación temp. Temp. regulation	Tension Voltage	Peso (kg.) Weight (kg.)
FTH 30 E	330 x 540 x 220	3	10	Liso / Smooth	Hierro / Iron	50° - 300° C	I+N~230V	23,7
FTHC 30 E	330 x 540 x 220	3	10	Liso / Smooth	Cromo Chromed	50° - 300° C	I+N~230V	23,7
FTR 30 E	330 x 540 x 220	3	10	Ranurado / Ribbed	Hierro / Iron	50° - 300° C	I+N~230V	23,7
FTRC 30 E	330 x 540 x 220	3	10	Ranurado / Ribbed	Cromo Chromed	50° - 300° C	I+N~230V	23,7
FTH 60 E	660 x 540 x 220	6	10	Liso / Smooth	Hierro / Iron	50° - 300° C	III+N~400V	40,6
FTHC 60 E	660 x 540 x 220	6	10	Liso / Smooth	Cromo Chromed	50° - 300° C	III+N~400V	40,6
FTHR 60 E	660 x 540 x 220	6	10	½ Liso ½ Ranurado / ½ Smooth ½ Ribbed	Hierro / Iron	50° - 300° C	III+N~400V	40,6
FTHRC 60 E	660 x 540 x 220	6	10	½ Liso ½ Ranurado / ½ Smooth ½ Ribbed	Cromo Chromed	50° - 300° C	III+N~400V	40,6
FTH 90 E	990 x 540 x 220	9	10	Liso / Smooth	Hierro / Iron	50° - 300° C	III+N~400V	69
FTHC 90 E	990 x 540 x 220	9	10	Liso / Smooth	Cromo Chromed	50° - 300° C	III+N~400V	69

FTH 30 G



FTRC 30 G



FTH 60 G



FTHRC 60 G



**CARACTERÍSTICAS TÉCNICAS**

Homologación CE.  
Ancho estándar GN de 33, 66 y 99 cm.  
1, 2 o 3 zonas de cocción independiente.  
Superficie lisa, ranurada o combinada.  
Opcion cromoduro.  
Cajon recoge grasa de 1,5 l.  
Gas natural o butano/Propano (GLP).

**TECHNICAL CHARACTERISTICS**

EC Approval  
GN standard width of 33, 66 & 99cm.  
1, 2 or 2 independent cooking zones.  
Smooth, ribbed or combined plate surfaces.  
Hard-chrome option for each type of plate available.  
Waste drawer of 1,5 litres.  
Connecting nozzles for both natural gas and propane / LPG.

Modelo Model	L x An x Alt L x W x H (mm.)	Potencia (kW) Power (kW)	Espesor placa Plate thickness (mm)	Acabado Surface	Encendido Ignition	Gas	Material Material	Peso (kg.) Weight (kg.)
FTH 30 G	330 x 600 x 220	4	10	Liso / Smooth	Chispero / Piezo	Natural/ GLP-LPG	Hierro / Iron	24,3
FTHC 30 G	330 x 600 x 220	4	10	Liso / Smooth	Chispero / Piezo	Natural/ GLP-LPG	Cromo / Chromed	24,3
FTR 30 G	330 x 600 x 220	4	10	Ranurado / Ribbed	Chispero / Piezo	Natural/ GLP-LPG	Hierro / Iron	24,3
FTRC 30 G	330 x 600 x 220	4	10	Ranurado / Ribbed	Chispero / Piezo	Natural/ GLP-LPG	Cromo / Chromed	24,3
FTH 60 G	660 x 600 x 220	8	10	Liso / Smooth	Chispero / Piezo	Natural/ GLP-LPG	Hierro / Iron	44,9
FTHC 60 G	660 x 600 x 220	8	10	Liso / Smooth	Chispero / Piezo	Natural/ GLP-LPG	Cromo / Chromed	44,9
FTHR 60 G	660 x 600 x 220	8	10	½ Liso ½ Ranurado / ½ Smooth ½ Ribbed	Chispero / Piezo	Natural/ GLP-LPG	Hierro / Iron	44,9
FTHRC 60 G	660 x 600 x 220	8	10	½ Liso ½ Ranurado / ½ Smooth ½ Ribbed	Chispero / Piezo	Natural/ GLP-LPG	Cromo / Chromed	44,9
FTH 90 G	990 x 600 x 220	12	10	Liso / Smooth	Chispero / Piezo	Natural/ GLP-LPG	Hierro / Iron	76,4
FTHC 90 G	990 x 600 x 220	12	10	Liso / Smooth	Chispero / Piezo	Natural/ GLP-LPG	Cromo / Chromed	76,4