



## Commercial Microwave Convection Oven

### Model No. NE-SCV3

Product Colour : Silver

Destination : United Kingdom

Destination : Continental Europe Countries



#### Control Panel (home screen)

##### Preheating Setting

- "Preheat temp." and "Cooling" are available.

##### Preheating State Indication Bar

- Displays the progress of the preheating.

##### Touch Screen (display)

- Tap on the screen directly to use the controls.
- Displays the menu list, cooking temperature and cooking time, the beep sound, etc.
- Do not touch the screen with a sharp object. Doing so will cause damage.

##### Stop/Reset Pad

- Press once to temporarily stop the cooking process. To resume cooking, press the Start pad.
- Press twice to clear your instructions (returns to the home screen) or cancel cooking.



##### Tools

##### Menu List

- You can switch between the picture list screen and the menu number select screen.

##### Back Pad


- Returns to the previous control screen so that settings can be changed.
- Unavailable after cooking has started

##### Start Pad


- After setting preheating or cooling, press this pad.
- If you press this button when the lamp is flashing, the preheating or cooking starts.

##### Lamp


- When the power plug is inserted, the lamp flashes, but this is not a malfunction.




Microondas




Grill




Convección



Grill y microondas



Convección y microondas



Convección y grill



# Specifications

<b>Power Source</b>	230–240 V, 50 Hz, Single phase	
<b>Required Power</b>	3600 W 15.8 A	
<b>Outlet</b>	16 A	
<b>Output</b>	<b>Microwave</b>	1050 W (IEC 60705)
	<b>Convection</b>	1465 W
	<b>Grill</b>	1915 W
<b>Frequency</b>	2450 MHz	
<b>Convection Temperature Range</b>	180–280 °C	
<b>Preheating Temperature Range</b>	Can be changed between 180–280 °C in 10 °C increments	
<b>Net Weight</b>	39 kg (including accessories)	
<b>Outer Dimensions (W×D×H)</b>	474 mm×565 mm×412 mm	
<b>Cavity Dimensions (W×D×H)</b>	270 mm×330 mm×110 mm	

Specifications subject to change without notice.  
Sound pressure level is less than 70 dB (A weighted).

