

## K43X

Stainless steel professional hood



### TARGET

Solutions: Coffee shops/Wine bars; Hotels; Restaurants/Pubs; Bakery/Pastry making; Frozen bakery industry; Food retail; Other food industry; Health and care; Catering and Institutions; QSR

### TYPE

Product family: Professional hood • Subfamily: Extraction • Hood Type: Mounted on oven • Design: Angled • Extraction: Recirculation • Electronic control: Yes • Suitable for: Oven series ALFA43 • Hood width: 60 cm

### AESTHETICS

Colour: Stainless steel • Material: Stainless steel

### PROGRAMME / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • 24h air filter function: Yes • Time-setting options: Automatic switch-off

### CONTROLS

Control setting: Touch control back-lighted White • Led color: White

## TECHNICAL FEATURES

No. of lights: 1 • Light type: LED • Light Power: 1,1 W • Dimmer mode: Yes • Light color temperature scale (°K): 4000 °K • Free outlet maximum capacity: 670 m<sup>3</sup>/h • Motor power: 230 W • No. of filters: 1 • Anti-grease filters: Buffle • Charcoal filters included: Yes • Filter replacement indicator: Yes • Vent outlet: 150 mm • Non return valve: Yes

## PERFORMANCE / ENERGY LABEL

## ELECTRICAL CONNECTION

Electrical connection rating: 232 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

## OPTIONAL ACCESSORIES

## ALSO AVAILABLE

## SPEED 1

Extraction rate IEC 61591: 240 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 49 dB(A) • Power: 132 W

## SPEED 2

Extraction rate IEC 61591: 321 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 54 dB(A) • Power: 155 W

## SPEED 3

Extraction rate IEC 61591: 429 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 63 dB(A) • Power: 169 W

## SPEED 4

## INTENSIVE SPEED

Extraction rate (IEC 61591): 594 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 70 dB(A) • Power: 193 W

