

THE CORE 2525(T) TECHNICAL DATA SHEET



Technical data

Model	CORE 2525	CORE 2525T
Stock code	8550	8555
Tank capacity	2 x 9-10 litres	2 x 9-10 litres
Dimensions*	500x600x850/900	500x600x850/900
Baskets*	202x285x135	202x285x135
Output per hour (frozen product)	40-52 kg/h	56-72 kg/h
Voltage	3N400V	3N400V
Heating power	14.4 kW	22 kW
Amperage	20A per phase	32A per phase
Heating element	2	2
Temperature range	95°C – 190° C	95°C – 190° C
Protection index	IPX4	IPX4
Net weight	78 kg	78 kg
Power cable	2.5m	2.5m
Frying surface per pan	W218 x D338mm	W218 x D338mm

* Width x Depth x Height (mm)



Supplied with lid, baskets, oil buckets, crumb filters, element lifting hook and mains cable



THE CORE 2525(T)

TECHNICAL DATA SHEET

Features and benefits

- Electromechanical thermostat with overheat protection
- Ergonomic thermostat knob for easy temperature control
- Integrated Sicotronic interface
- Intelligent adjustment for optimised performance and precise temperature control (+/- 6°C)
- Maximum insulation to optimise efficiency and heat retention, minimising energy loss
- Cool zone for waste collection below the heating element, slowing down oil degradation
- Fryer can be heated for cleaning with water (95°C)
- Rounded corners and a pivoting heating element, with an intermediate stop position, for easy cleaning
- Folding lid for easy storage (inside fryer door)
- MELT Position: melts solid fat without burning it
- Easy to locate element RESET button
- High quality components and finish to meet the highest standards
- Stainless steel, strong and durable
- Adjustable height castors with fixed castors on rear
- Turbo option, ideal for frying frozen food
- Swiss Made: manufactured at the Valentine Fabrique factory in Romanel-sur-Morges
- IPX4 rating / 3-year warranty / 20-year tank warranty
- 20-year availability of spare parts

Options

- Built-in installation
- Turbo
- Other voltages available on request

Accessories

- Microfilter with support frame
- Fishplate
- Batter bowl
- Splashguard
- Interlock channel
- VITO oil filtration
- VITO oil tester

Certifications

- CB, UL, CE, UKCA

Technical drawings (mm)

